

R-600a Refrigerant Grade Isobutane




R-600a is refrigerant grade isobutane that is growing in use due to its low environmental impact. R-600a is highly flammable and is only acceptable for use by the EPA in small charge applications. It is illegal to convert any existing ACR system designed for use with CFCs, HCFCs, or HFCs, to R-600a, or any other flammable refrigerant. Always refer to the EPA's SNAP List (Significant New Alternatives Policy) for a complete list of acceptable uses. Go to www.EPA.gov and search SNAP.

ASHRAE Designation	Trade Name	Chemical Formula	Liq °F NBP	Chemical Formula
R-600a	na	isobutane	10.9	HC

**ICOR Part#:
R-600a-14**

Sold 20 cans per case



**Can Tap Valve
Part#: HC-VLV**

EQUIPPED WITH SELF-SEALING LID

Safety Class	Critical °F	ODP	GWP 100 years	Oil	Application
A3	305	0	3.3	All	Small ACR systems

ICOR R-600a is packaged in 14.82 oz D.O.T. certified disposable cans and sold in case lots only.

For more information or to find a distributor near you, visit www.icorinternational.com or call 1-800-497-6805.

For Free Online Training at ICOR's Virtual Training Center, visit www.icorvtc.com.

ICOR
INTERNATIONAL
"making your life easier™"

R600ASS